

ISOVOLTINE IIA-TP



Insulating Oil



Inhibited mixed base mineral insulating oil

APPLICATIONS

Insulating oil

- **ISOVOLTINE IIA-TP** oil is an inhibited mixed base mineral oil for transformers, rheostats and circuit breakers using mineral oils

SPECIFICATIONS

International specifications

- ASTM D 3487 Type II
- BS 148 Class IA and IIA

ADVANTAGES

- High insulating capability
- Low viscosity for effective cooling
- Very good oxidation resistance giving long life
- High flash point to eliminate any risk of fire
- Very good demulsification ensuring good water separation in case of accidental pollution
- Absolutely no impurities such as dissolved gas, water or suspended

TYPICAL CHARACTERISTICS	ASTM METHODS	UNITS	SPECIFICATIONS	TYPICAL
Density at 15°C	D 1298	Kg/m ³	Max. 910	825
Viscosity at 40°C	D 445	mm ² /s	Max. 12.0	7.87
Pour point	D 97	°C	Max. -40	-45
Cleveland open cup flash point	D 92	°C	Min. 145	158
Dielectric strength (untreated oil)	D 1816	KV	Min. 35	50
Power Factor at 60Hz 100°C	D 924	%	Max.0.3	0.1

Above characteristics are mean values given as an information

Total Lubricants Taiwan Ltd.
ISOVOLTINE IIA-TP

